

Principal dimensions			Designation	Options of design
d (mm)	D (mm)	B (mm)		
40	68	21	NN3008	K
45	75	23	NN3009	K
50	80	23	NN3010	K
55	90	26	NN3011	K
60	95	26	NN3012	K
65	100	26	NN3013	K
70	110	30	NN3014	K, P4, W33
75	115	30	NN3015	K
80	125	34	NN3016	K, P4, W33
85	130	34	NN3017	K
90	140	37	NN3018	K
95	145	37	NN3019	K
100	150	37	NN3020	K
100	140	40	NNU4920	K
100	140	40	NNCF4920V	
105	145	40	NNU4921	K
110	170	80	NNCF5022V	
110	150	40	NNU4922	K
110	170	45	NN3022	K
120	165	45	NNCF4924V	
120	180	46	NN3024	K
120	165	45	NNU4924	K
130	200	95	NNCF5026V	
130	200	52	NN3026	K, W33
130	180	50	NNU4926	K
140	210	95	NNCF5028V	
140	210	53	NN3028	K
140	190	50	NNU4928	K
150	210	60	NNCF4930V	
150	210	60	NNU4930	K
150	225	56	NN3030	K
160	220	60	NNCF4932V	
160	220	60	NNU4932	K
160	240	60	NN3032	K, W33
170	230	60	NNU4934	K
170	260	67	NN3034	K
170	230	60	NNCF4934V	
180	250	69	NNU4936	K, W33
180	280	74	NN3036	K
190	260	69	NNU4938	K, W33, P5
190	290	75	NN3038	K
190	290	136	NNCF5038V	
200	280	80	NNU4940	K, W33
200	310	82	NN3040	K, W33
220	300	80	NNU4944	K
220	340	90	NN3044	K, W33
240	300	60	NNCF4848V	
240	320	80	NNU4948	K

240	360	92	NN3048	K, W33
260	360	100	NNU4952	K, W33, C4
260	400	104	NN3052	K
260	400	190	NNCF5052V	
280	380	100	NNU4956	K
280	420	106	NN3056	K, W33
280	350	69	NNCF4856V	
300	420	118	NNU4960	K
300	460	118	NN3060	K, W33
300	420	118	NNCF4960V	
320	440	118	NNU4964	K, P5, W33
320	480	121	NN3064	K, W33
340	420	80	NNCF4868V	
340	520	133	NN3068	K
360	540	134	NN3072	K
380	560	135	NN3076	K, W33
400	600	148	NN3080	K, W33
400	540	106	NN3980	K, W33
420	620	150	NN3084	K
420	620	200	NNU4084	K, W33
460	620	160	NNU4992	K, W33
460	680	163	NN3092	K, W33
480	700	165	NN3096	K, W33
500	670	170	NNU49/500	K, W33
500	720	167	NN30/500	K, W33
530	710	136	NN39/530	K, W33
530	710	180	NN49/530	K, W33
560	750	140	NN39/560	K, W33
600	800	200	NN49/600	K, W33