

Principal dimensions			Designation	Options of fuctional characteristics sealing/locating/cage/lubricating/more
d (mm)	D (mm)	B (mm)		
12	30	8	16101	RS, 2RS, Z, ZZ
12	28	8	6001	RS, 2RS, Z, ZZ
12	21	5	61801	2RS, ZZ
12	24	6	61901	2RS, ZZ
12	32	10	6201	RS, 2RS, Z, ZZ
12	37	12	6301	RS, 2RS, Z, ZZ
12.7	33.338	9.525	RLS 4	2RS, ZZ
15	32	8	16002	Z, ZZ
15	32	9	6002	RS, 2RS, Z, ZZ
15	24	5	61802	2RS, ZZ
15	35	11	6202	RS, 2RS, Z, ZZ, NR
15	42	13	6302	RS, 2RS, Z, ZZ
15.875	39.688	11.112	RLS 5	2RS, ZZ
17	35	10	6003	RS, 2RS, Z, ZZ
17	47	14	6303	RS, 2RS, Z, ZZ, NR
20	47	14	6204	RS, 2RS, Z, ZZ, N, NR
20	52	15	6304	RS, 2RS, Z, ZZ, N, NR
22.225	50.8	14.288	RLS 7	-
25	47	12	6005	RS, 2RS, Z, ZZ, N, NR
25	37	7	61805	2RS, 2RZ
28	58	16	62/28	-
30	72	19	306	Z, ZZ, NR
30	42	7	61806	2RS, 2RZ
30	62	16	6206	RS, 2RS, Z, ZZ, N, NR
30	72	19	6306	RS, 2RS, Z, ZZ, N, NR
34.925	88.9	22.225	RLS 11	-
35	80	21	6307	RS, 2RS, Z, ZZ, N, NR
40	68	9	16008	-
45	75	16	6009	RS, 2RS, Z, ZZ
45	120	19	6409	NR
45	100	25	6309	RS, 2RS, Z, ZZ, N, NR
50	80	16	6010	RS, 2RS, Z, ZZ, N, NR
50	110	27	6310	RS, 2RS, Z, ZZ, N, NR
55	90	18	6011	RS, 2RS, Z, ZZ, N, NR, M
55	100	21	6211	RS, 2RS, Z, ZZ, N, NR, M
60	78	10	61812	2RS, 2RZ
65	100	18	6013	RS, 2RS, Z, ZZ, N, NR, M
70	150	35	6314	RS, 2RS, Z, ZZ, N, NR, M
76.2	177.8	39.688	RMS 24	-
80	200	48	6416	-
85	150	28	6217	RS, 2RS, Z, ZZ, N, NR, M
90	140	16	10618	-
95	200	45	6319	RS, 2RS, Z, ZZ, N, NR, M
100	180	34	6220	RS, 2RS, Z, ZZ, N, NR, M
105	160	26	6021	RS, 2RS, Z, ZZ, N, NR
110	170	28	6022	RS, 2RS, Z, ZZ, N, NR, M
110	240	50	6322	M
120	180	19	10624	-
120	18	28	6024	RS, 2RS, Z, ZZ, N, NR

DEEP GROOVE BALL BEARINGS

KIHOI INDUSTRY

120	260	55	6324	2RS, M
130	230	40	6226	RS, 2RS, Z, ZZ, N, M
140	210	33	6028	RS, 2RS, Z, ZZ, M
150	225	35	6030	2RS, ZZ, M
160	340	68	6332	M
170	215	22	61834	-
180	280	46	6036	M
220	340	56	6044	M
240	440	72	6248	M
260	400	65	6052	M
260	320	28	61852	M
260	480	80	6252	M
280	420	65	6056	M
320	480	74	6064	M
360	540	82	6072	M
440	650	94	6088	M
500	670	78	619/500	M
560	680	56	618/560	M
670	980	136	60/670	M
950	1150	90	618/950	M